

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A heater comprising:

a solid graphite body configured from a solid self standing body of graphite in into a pattern for an electrical flow path defining at least one zone of an electrical heating circuit, said electrical circuit comprising terminal ends for terminals to be electrically connected to said electrical flow path, said graphite body having at least one heating surface,

a coating layer encapsulating said patterned graphite body, said coating layer comprises at least one of a nitride, carbide, carbonitride or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof; and

a substantially continuous surface layer disposed on said heating surface; said surface layer comprising at least one of a nitride, carbide, carbonitride or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof.

Claim 2 (currently amended): A heater comprising:

a graphite body configured in from a solid self standing body of graphite into a pattern for an electrical flow path defining at least one zone of an electrical heating circuit, said electrical circuit comprising terminal ends for terminals to be electrically connected to said electrical flow path,

wherein a first coating layer is applied to at least one surface of said graphite body prior to being configured to form the electrical flow path pattern, said first coating layer comprising as least one of a nitride, carbide, carbonitride, or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof;

a second coating layer disposed on said patterned graphite body for a substantially continuous heating surface, said second coating layer comprising at least one of a nitride, carbide, carbonitride or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof.

Claim 3 (original): The heater of claim 2, wherein said first coating layer encapsulates the graphite body.

Claim 4 (original): The heater of claim 2, wherein said second coating layer is applied onto the surface of the patterned graphite body that is not coated with the first coating layer, for a continuous heating surface.

Appl. No. 10/687,212
Amdt. dated July 27, 2005
Reply to Office action of May 27, 2005

Claim 5 (original): The heater of claim 2, wherein said electrical flow path has at least one of a spiral pattern, a serpentine pattern, a helical pattern, a zigzag pattern, a continuous labyrinthine pattern, a spirally coiled pattern, a swirled pattern, a randomly convoluted pattern, and combinations thereof.

Claim 6 (currently amended): The heater of claim 2, wherein said coating layer and said second coating layer are the same material, selected from ~~on~~ one of a nitride, carbide, carbonitride, or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and combinations thereof.

Claim 7 (original): The heater of claim 2, wherein said first coating layer comprises at least one of pyrolytic boron nitride, aluminum nitride, and complexes thereof.

Claim 8 (original): The heater of claim 2, wherein said second coating layer comprises at least one of pyrolytic boron nitride, aluminum nitride, and complexes thereof.

Claim 9 (original): The heater of claim 2, wherein said first coating layer and said second coating layer are formed by a technique selected from a physical vapor deposition, a chemical vapor deposition, a spraying process using an air sprayer, a painting process employing a roller, a thermal spray process, a thermal injection process, and combinations thereof.

Claim 10 (original): The heater of claim 2, wherein said first coating layer and said second coating layer are deposited using the same technique.

Claim 11 (original): The heater of claim 10, wherein said first coating layer and said second coating layer are deposited via a chemical vapor deposition process.

Claim 12 (original): The heater of claim 2, wherein the pattern in said graphite body is configured using a technique selected from one of micro machining, micro-brading, laser cutting, chemical etching, and e-beam etching.

Claim 13 (original): The heater of claim 2, wherein said graphite body is one of a disk, a platen, and a cylinder.

Claim 14 (currently amended): A method for forming a heater, said process comprising the steps of:

- a) providing a solid graphite body ~~coated on~~ configured from a solid self standing body of graphite with at least one surface coated with a first coating layer comprising at least one of a nitride, carbide, carbonitride, or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof;
- b) configuring a pattern for an electrical flow path defining at least one zone of

- an electrical heating circuit in said coated graphite heater;
- c) coating said patterned graphite heater with a second coating layer comprising at least one of a nitride, carbide, carbonitride, or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof.

Claim 15 (original): The method of claim 14, wherein said electrical circuit pattern comprises terminal ends for terminals to be electrically connected forming an electrical flow path.

Claim 16 (original): The method of claim 14, wherein said first coating layer and said second coating layer are of the same material comprising at least one of a nitride, carbide, carbonitride or oxynitride of elements selected from a group consisting of B, Al, Si, Ga, refractory hard metals, transition metals, and rare earth metals, or complexes and/or combinations thereof.

Claim 17 (original): The method of claim 14, wherein said electrical flow path has one of a spiral pattern, a serpentine pattern, a helical pattern, a zigzag pattern, a continuous labyrinthine pattern, a spirally coiled pattern, a swirled pattern, a randomly convoluted pattern, and combinations thereof.

Appl. No. 10/687,212
Amdt. dated July 27, 2005
Reply to Office action of May 27, 2005

Claim 18. (original): The method of claim 14, wherein said first coating layer and said second coating layer are formed by a technique selected from a physical vapor deposition, a chemical vapor deposition, a spraying process using an air sprayer, a painting process employing a roller, a thermal spray process, a thermal injection process, and combinations thereof.

Claim 19 (original): The method of claim 18, wherein said first coating layer and said second coating layer are formed via chemical vapor deposition.

Claim 20 (original): The method of claim 14, wherein the pattern in said graphite body is configured using a technique selected from one of micro machining, micro-brading, laser cutting, chemical etching, and e-beam etching.

Claim 21 (original): The method of claim 14, wherein said graphite body is one of a disk, a platen, and a cylinder.

Claim 22 (currently amended): The method of claim 14, further comprising the step of providing terminalends for terminals to be electrically connected to said electrical flow path.

Claim 23 (original): Silicon wafers processed using the heater of claim 1.

Claim 24 (original): Silicon wafers processed using the heater of claim 2.